

BHAGWAN MOVER

LANDING BARGE



BUILT:

PIASAU SLIPWAYS, MALAYSIA
MARCH 2009

FLAG:

AUSTRALIAN

CLASSIFICATION:

BUREAU VERITAS - UNRESTRICTED

IMO NUMBER: 9542001
CALL SIGN: VNW6163

DIMENSIONS:

LENGTH OVERALL	48.00 M	
BEAM	12.80 M	
DEPTH MOULDED	3.2 M	
DRAFT (LOADED)	2.4 M	OR LESS
GRT	625	TONNE
NT	188	TONNE
DEADWEIGHT	550	TONNE

MACHINERY:

MAIN ENGINES 2 X CUMMINS K19, 480 kW
KEELED COOLED
ELECTRICAL GENERATION 2 X CUMMINS

SPEED AND CONSUMPTION:

FULL OPERATING 10 KNOTS @ 160 LITRES / HR
IN PORT 300 LITRES PER DAY

CAPACITIES:

MAXIMUM DECK CARGO	350 TONNE (AT MINIMUM FUEL AND WATER)
CLEAR DECK AREA (MAIN DECK)	27 M (L) X 11 M (B)
(BOW RAMP)	7 M (L) X 8 M (B)
DECK AREA	325 M ²
FUEL	400,000 LITRES
WATER	290,000 LITRES
DECK LOAD RATING	MAXIMUM 10 TONNE PER M ²

CARGO DISCHARGE PUMPS:

FUEL CARGO	80 M ³ / HR @ 6.0 BAR
FRESHWATER	80 M ³ / HR @ 4.0 BAR

HULL:

STEEL
BOW RAMP CONFIGURED TO ACCOMMODATE ROLL-ON ROLL-OFF LOADING OF 20 FT SHIPPING CONTAINERS

BRIDGE:

FULLY ENCLOSED HELM POSITION
RADAR FURUNO 86 NM X BAND
AIS FURUNO FA-150
GMDSS FURUNO AREA A3
DEPTH SOUNDER FURUNO FE-700
GYRO COMPASS ANSCHUTZ STD22
AUTO PILOT ANSCHUTZ NP60
ELECTRONIC CHART
PLOTTER MAXSEA
GPS FURUNO GP37
SAT PHONE FLEET BROADBAND 250

ACCOMMODATION:

BERTHS FOR 9
FULLY AIRCONDITIONED

POLLUTION CONTROL:

MARPOL COMPLIANT SEWAGE TREATMENT PLANT AND HOLDING TANK
OILY WATER SEPARATOR WITH HOLDING TANKS FOR WASTE OIL AND DIRTY BILGE
VESSEL IS CONFIGURED FOR ZERO DISCHARGE

SAFETY, FIRE FIGHTING AND LIFESAVING EQUIPMENT:

VESSEL WILL COMPLY TO SOLAS REQUIREMENTS.

Servicing the Offshore Oil and Gas Industry